Cambridge Assessment International Education

Cambridge International AS & A Level

COMPUTER SCIENCE **9618/21**

Paper 2 Fundamental Problem-solving and Programming Skills **October/November 2021**

INSERT **2 hours**

2390708169-I

INFORMATION

- This insert contains all the resources referred to in the questions.
- You may annotate this insert and use the blank spaces for planning. **Do not write your answers** on the insert.

This document has **4** pages.

DC (PQ) 222283
© UCLES 2021

[Turn over

Note: An error occurs if a function call is not properly formed, or if the parameters are incorrect.

STRING Functions

`LEFT(ThisString : STRING, x : INTEGER) RETURNS STRING`
returns leftmost `x` characters from `ThisString`

Example: `LEFT("ABCDEFGH", 3)` returns `"ABC"`

`RIGHT(ThisString: STRING, x : INTEGER) RETURNS STRING`
returns rightmost `x` characters from `ThisString`

Example: `RIGHT("ABCDEFGH", 3)` returns `"FGH"`

`MID(ThisString : STRING, x : INTEGER, y : INTEGER) RETURNS STRING`
returns a string of length `y` starting at position `x` from `ThisString`

Example: `MID("ABCDEFGH", 2, 3)` returns `"BCD"`

`LENGTH(ThisString : STRING) RETURNS INTEGER`
returns the integer value representing the length of `ThisString`

Example: `LENGTH("Happy Days")` returns `10`

`LCASE(ThisChar : CHAR) RETURNS CHAR`
returns the character value representing the lower case equivalent of `ThisChar`
Alphabetic characters that are not upper case are unchanged.

Example: `LCASE('W')` returns `'w'`

`UCASE(ThisChar : CHAR) RETURNS CHAR`
returns the character value representing the upper case equivalent of `ThisChar`
Alphabetic characters that are not lower case are unchanged.

Example: `UCASE('a')` returns `'A'`

`TO_UPPER(ThisString : STRING) RETURNS STRING`
returns a string formed by converting all characters of `ThisString` to upper case.

Example: `TO_UPPER("Error 803")` returns `"ERROR 803"`

`TO_LOWER(ThisString : STRING) RETURNS STRING`
returns a string formed by converting all characters of `ThisString` to lower case.

Example: `TO_LOWER("JIM 803")` returns `"jim 803"`

© UCLES 2021

`NUM_TO_STR(x : <data type1>) RETURNS <data type2>`
returns a string representation of a numeric value.

Note: `<data type1>` may be `REAL` or `INTEGER`
`<data type2>` may be `CHAR` or `STRING`

Example: `NUM_TO_STR(87.5)` returns `"87.5"`

`STR_TO_NUM(x : <data type1>) RETURNS <data type2>`
returns a numeric representation of a string.

Note: `<data type1>` may be `CHAR` or `STRING`
`<data type2>` may be `REAL` or `INTEGER`

Example: `STR_TO_NUM("23.45")` returns `23.45`

`IS_NUM(ThisString : STRING) RETURNS BOOLEAN`
returns the value `TRUE` if `ThisString` represents a valid numeric value.

Example 1: `IS_NUM("12.36")` returns `TRUE`
Example 2: `IS_NUM("-12.36")` returns `TRUE`
Example 3: `IS_NUM("12.3a")` returns `FALSE`

`ASC(ThisChar : CHAR) RETURNS INTEGER`
returns an integer value (the ASCII value) of `ThisChar`

Example: `ASC('A')` returns `65`

`CHR(x : INTEGER) RETURNS CHAR`
returns the character whose integer value (the ASCII value) is `x`

Example: `CHR(87)` returns `'W'`

NUMERIC Functions

`INT(x : REAL) RETURNS INTEGER`
returns the integer part of `x`

Example: `INT(27.5415)` returns `27`

`RAND(x : INTEGER) RETURNS REAL`
returns a real number in the range `0` to `x` (**not** inclusive of `x`).

Example: `RAND(87)` could return `35.43`

OTHER Functions

`EOF(FileName : STRING) RETURNS BOOLEAN`
returns `TRUE` if there are no more lines to be read from file `FileName`

Note: The function will generate an error if the file is not already open in `READ` mode.

Note: An error occurs if an operator with a value of an incorrect type is used.

OPERATORS

`&`	Concatenates (joins) two strings Example: `"Summer" & " " & "Pudding"` evaluates to "Summer Pudding"
`AND`	Performs a logical `AND` on two Boolean values Example: `TRUE AND FALSE` evaluates to `FALSE`
`OR`	Performs a logical `OR` on two Boolean values Example: `TRUE OR FALSE` evaluates to `TRUE`
`NOT`	Performs a logical `NOT` on a Boolean value Example: `NOT TRUE` evaluates to `FALSE`
`MOD`	Finds the remainder when one number is divided by another Example: `10 MOD 3` evaluates to `1`
`DIV`	Finds the quotient when one number is divided by another Example: `10 DIV 3` evaluates to `3`

Permission to reproduce items where third-party owned material protected by copyright is included has been sought and cleared where possible. Every reasonable effort has been made by the publisher (UCLES) to trace copyright holders, but if any items requiring clearance have unwittingly been included, the publisher will be pleased to make amends at the earliest possible opportunity.

To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced online in the Cambridge Assessment International Education Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download at www.cambridgeinternational.org after the live examination series.

Cambridge Assessment International Education is part of the Cambridge Assessment Group. Cambridge Assessment is the brand name of the University of Cambridge Local Examinations Syndicate (UCLES), which itself is a department of the University of Cambridge.

© UCLES 2021